

SLP060-12

High Efficiency Multicrystalline PV Module

Electrical Characteristics	SLP060-12
Product code	060011202
Maximum power (Pmax)	60W
Voltage at Pmax (Vmp)	17.4V
Current at Pmax (Imp)	3.44A
Open-circuit voltage (Voc)	21.5V
Short-circuit current (Isc)	3.78A
Temperature coefficient of Voc	-80 ± 10 mV/°C
Temperature coefficient of Isc	$(0.065 \pm 0.015)\%$ / °C
Temperature coefficient of power	$-(0.5 \pm 0.05)\%$ / °C
NOCT (Air 20°C; Sun 0.8kW/m ² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	+10%/- 5%

*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

*NOCT: Nominal operating cell temperature (the data is only for reference)




Module Diagram

Dimensions in brackets are in inches.

Un-bracketed dimensions are in millimeters.


Unit: mm[in.]



Features

- Nominal 12V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

Characteristics



SLP060-12 I-V Curves

Specifications	SLP060-12
Cells	Polycrystalline silicon solar cell
No. of cells and connections	36(4X9)
Module dimension	774mm[30.47in.]x675mm[26.57in.]x35mm[1.38in.]
Weight	6.7kg[14.77lbs]
Packing information(Carton)	820mm[32.28in.]x720mm[28.35in.]x105mm[4.13in.](2pcs/ctn)

*Limited warranty: 5-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us.

*Specifications are subject to change without notice at any time.